

Han 24B-HTE-CL-M40



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 19 30 024 0488 |
| Specification | Han 24B-HTE-CL-M40 |
| HARTING eCatalogue | https://b2b.harting.com/19300240488 |

Identification

| | |
|--------------------------|--------------------|
| Category | Hoods/Housings |
| Series of hoods/housings | Han [®] B |
| Type of hood/housing | Hood |
| Type | High construction |

Version

| | |
|----------------------|---|
| Size | 24 B |
| Version | Top entry |
| Cable entry | 1x M40 |
| Locking type | Central locking lever (on the hood) |
| Field of application | Standard hoods/housings for industrial connectors |

Technical characteristics

| | |
|--|--|
| Limiting temperature | -40 ... +125 °C |
| Note on the limiting temperature | For use as a connector according to IEC 61984. |
| Degree of protection acc. to IEC 60529 | IP65 |
| Type rating acc. to UL 50 / UL 50E | 4 4X 12 |

Material properties

| | |
|-------------------------|----------------------|
| Material (hood/housing) | Aluminium die-cast |
| Surface (hood/housing) | Powder-coated |
| Colour (hood/housing) | RAL 7037 (dust grey) |



Pushing Performance
Since 1945

Material properties

| | |
|--------------------|-----------------|
| Material (locking) | Stainless steel |
|--------------------|-----------------|

Specifications and approvals

| | |
|-----------|--------|
| Approvals | DNV GL |
| CE | Yes |

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 1 |
| Net weight | 425 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| GTIN | 5713140165151 |
| eCl@ss | 27440202 Shell for industrial connectors |
