

## KSP

Material: Weich-PVC  
Farbe: silbergrau  
Einsatztemperatur: -25 °C bis 80 °C  
Schutzart: IP 68

Material: soft PVC  
Colour: silver-grey  
Temperature range: -25 °C to 80 °C  
Protection type: IP 68

**481.00**

Innen- / Außen-Ø Inside / outside dia. mm	Rollenlänge Coil length m	empfohlene Versch. Recomm. connectors	HUGRO No.
7 x 10	50		<b>481.0710</b>
10,5 x 13,5	50	218.xx12	<b>481.1114</b>
13,5 x 16,5	50	218.xx14	<b>481.1417</b>
15 x 18,5	50	218.xx16	<b>481.1519</b>
17 x 20,5	50	218.xx16	<b>481.1721</b>
22 x 26,5	50	218.xx21	<b>481.2227</b>
29,5 x 35,5	25	218.xx29	<b>481.3036</b>
38 x 44,5	25	218.xx37	<b>481.3845</b>

### Eigenschaften:

- flexibel, innen und außen glatt
- luft- und flüssigkeitsdicht

### Properties:

- flexible, smooth inside and outside surface
- airtight and liquidproof



dgl., jedoch mit Umflechtung aus verzinktem Stahldraht

dito, but with galvanized steel wire braiding

## KSP-EU

**485.00**

Innen- / Außen-Ø Inside / outside dia. mm	Rollenlänge Coil length m	empfohlene Versch. Recomm. connectors	HUGRO No.
6 x 10	50		<b>485.0610</b>
9 x 14	50	218.xx09	<b>485.0914</b>
12 x 17	50	218.xx12	<b>485.1217</b>
14 x 19	50	218.xx14	<b>485.1419</b>
16 x 21	50	218.xx16	<b>485.1621</b>
21 x 27	50	218.xx21	<b>485.2127</b>
28 x 36	25	218.xx29	<b>485.2836</b>
37 x 46	25	218.xx37	<b>485.3746</b>

### Eigenschaften:

- flexibel, innen glatt
- luft- und flüssigkeitsdicht
- Abschirmung sowie Schutz vor heißen Spänen

### Characteristics:

- flexible, smooth inside surface
- airtight and liquidproof
- shielding as well as protection against hot swarfs

