

Material: Messing vernickelt
 Schutzart: IP 54


 Material: brass, nickel-plated
 Protection type: IP 54

526.00

Serie 527.00:
 O-Ring: NBR
 Einsatztemperatur: -20° bis 100 °C
 Schutzart: IP 68
Series 527.00:
 O-ring: NBR
 Temperature range: -20 °C to 100 °C
 Protection type: IP 68

527.00

Gewinde Thread AG	Gewinde Thread IG	 mm	H mm	GL mm	ohne O-Ring without O-ring HUGRO No.	mit O-Ring with O-ring HUGRO No.
M 8 x 1,25	M 6 x 1	11	13	5		527.0806
M 10 x 1,5	M 6 x 1	13	8	5		527.1006
M 10 x 1,5	M 8 x 1,25	13	13	5		527.1008
M 12 x 1,5	M 8 x 1,25	15	8	5		527.1508
M 12 x 1,5	M 10 x 1,5	15	13	5		527.1510
M 16 x 1,5	M 10 x 1,5	18	8	5		527.1710
M 16 x 1,5	M 12 x 1,5	18	8,5	6	526.1715	527.1715
M 20 x 1,5	M 12 x 1,5	22	9	6,5	526.2015	527.2015
M 20 x 1,5	M 16 x 1,5	22	29	6	526.2017	527.2017
M 25 x 1,5	M 16 x 1,5	28	10	7	526.2517	527.2517
M 25 x 1,5	M 20 x 1,5	28	10	7	526.2520	527.2520
M 32 x 1,5	M 20 x 1,5	35	11,5	8	526.3220	527.3220
M 32 x 1,5	M 25 x 1,5	35	11,5	8	526.3225	527.3225
M 40 x 1,5	M 25 x 1,5	43	12,5	9	526.4025	527.4025
M 40 x 1,5	M 32 x 1,5	43	12,5	9	526.4032	527.4032
M 50 x 1,5	M 32 x 1,5	54	14	10	526.5032	527.5032
M 50 x 1,5	M 40 x 1,5	54	14	10	526.5040	527.5040
M 63 x 1,5	M 40 x 1,5	68	14	10	526.6340	527.6340
M 63 x 1,5	M 50 x 1,5	68	14	10	526.6350	527.6350
M 72 x 2	M 63 x 1,5	80	18	10	526.7263	527.7263
M 75 x 1,5	M 50 x 1,5	80	17	11		527.7450
M 75 x 1,5	M 63 x 1,5	80	17	11		527.7463
M 80 x 2	M 63 x 1,5	90	18	10	526.8A63	527.8A63
M 80 x 2	M 75 x 1,5	90	18	10		527.8A74
Pg 9	Pg 7	17	8,8	6	526.0907	527.0907
Pg 11	Pg 7	20	9	6	526.1107	527.1107
Pg 11	Pg 9	20	9	6	526.1109	527.1109
Pg 13,5	Pg 7	22	9,5	6,5	526.1307	527.1307
Pg 13,5	Pg 9	22	9,5	6,5	526.1309	527.1309
Pg 13,5	Pg 11	22	9,5	6,5	526.1311	527.1311
Pg 16	Pg 7	24	9,5	6,5	526.1607	527.1607
Pg 16	Pg 9	24	9,5	6,5	526.1609	527.1609
Pg 16	Pg 11	24	9,5	6,5	526.1611	527.1611
Pg 16	Pg 13,5	24	9,5	6,5	526.1613	527.1613
Pg 21	Pg 11	30	10,3	7	526.2111	527.2111
Pg 21	Pg 13,5	30	10,3	7	526.2113	527.2113
Pg 21	Pg 16	30	10,3	7	526.2116	527.2116
Pg 29	Pg 13,5	40	11,5	8	526.2913	527.2913
Pg 29	Pg 16	40	11,5	8	526.2916	527.2916
Pg 29	Pg 21	40	11,5	8	526.2921	527.2921
Pg 36	Pg 21	50	12,5	9	526.3621	527.3621
Pg 36	Pg 29	50	12,5	9	526.3629	527.3629
Pg 42	Pg 29	57	13,5	10	526.4229	527.4229
Pg 42	Pg 36	57	13,5	10	526.4236	527.4236
Pg 48	Pg 36	64	13,5	10	526.4836	527.4836
Pg 48	Pg 42	64	13,5	10	526.4842	527.4842

Auf Anfrage:
 für höhere Temperaturen bis 200° C
 in Edelstahl (1.4305)
On request:
 for higher temperature up to 200° C
 in stainless steel (1.4305)


526.00



527.00