

Progress-M (NPT)

Material: Messing vernickelt
 Dichteinsatz: TPE
 Einsatztemperatur: -40 °C bis 100 °C
 Schutzart: IP 68



Material: brass, nickel-plated
 Sealing insert: TPE
 Temperature range: -40 °C to 100 °C
 Protection type: IP 68


101.00

Weitere internationale Zulassungen vorhanden

Further international approvals available



Gewinde Entry Thread AG			H mm	GL mm	HUGRO No.
kurzer, einteiliger Dichteinsatz / short, one-piece sealing insert					
1/8" NPT	3 - 4	13	15	8	101.0304.00
1/8" NPT	4 - 6	13	15	8	101.0306.00
1/4" NPT	3,5 - 5	15	17	12	101.0405.00
1/4" NPT	5 - 6,5	15	17	12	101.0406.00
1/4" NPT	6,5 - 8	15	17	12	101.0408.00
3/8" NPT	3,5 - 4,5	18	20	12	101.3904.00
3/8" NPT	4,5 - 6	18	20	12	101.3906.00
3/8" NPT	6 - 8	18	20	12	101.3908.00
3/8" NPT	8 - 10,5	18	22	12	101.3910.00
1/2" NPT	6 - 8	24	21	15	101.1908.00
1/2" NPT	8 - 11	24	21	15	101.1911.00
1/2" NPT	11 - 15	24	23	15	101.1915.00
3/4" NPT	9,5 - 12,5	30	28	15	101.3512.00
3/4" NPT	12,5 - 16	30	28	15	101.3516.00
3/4" NPT	16 - 20,5	30	28	15	101.3520.00
1" NPT	14 - 17	36	28	20	101.7517.00
1" NPT	17 - 21	36	28	20	101.7521.00
1" NPT	21 - 25,5	36	28	20	101.7525.00
1 1/4" NPT	20 - 24	46	31	20	101.7624.00
1 1/4" NPT	24 - 28,5	46	31	20	101.7628.00
1 1/4" NPT	28,5 - 33	46	31	20	101.7633.00
1 1/2" NPT	29 - 33	55	34	22	101.7733.00
1 1/2" NPT	33 - 37	55	34	22	101.7737.00
1 1/2" NPT	37 - 41	55	34	22	101.7741.00
2" NPT	35 - 40	70	37	22	101.7840.00
2" NPT	40 - 46	70	37	22	101.7846.00
2" NPT	46 - 52	70	37	22	101.7852.00
kurzer, zweiteiliger Dichteinsatz / short, two-piece sealing insert					
3/8" NPT	6 - 10,5	18	22	12	101.3902.00
1/2" NPT	8 - 15	24	23	15	101.1902.00
3/4" NPT	12,5 - 20,5	30	28	15	101.3502.00
1" NPT	17 - 25,5	36	28	20	101.7502.00
1 1/4" NPT	24 - 33	46	31	20	101.7602.00
1 1/2" NPT	33 - 41	55	34	22	101.7702.00
2" NPT	40 - 52	70	37	22	101.7802.00



Hygienic

Cable Glands

EMC Protection

Ex Protection

Conduit Protection Syst.

Accessories

Technical Appendix

Article Number Index