

TECHNISCHE DATEN:

Aufbau

Reduktion	Polyamid PA6
Außengewinde	metrisch, nach EN 60423
Innengewinde	metrisch, nach EN 60423

Eigenschaften

- zum Reduzieren einer Gewinde- oder Durchgangsbohrung auf eine kleinere Gewindegröße

Gruppe (Zone)	II 2 G (1,2)	II 2 D (21,22)
Kennzeichnung	Ex e IIC Gb	Ex tb IIIC Db
Temperaturbereich	-55 °C / +70 °C	
Schutzart	IP66, abhängig von der Kombination mit anderen Komponenten	
Prüfnorm	EN IEC 60079-0:2018, IEC 60079-0:2017 EN IEC 60079-7:2015+A1, IEC 60079-7:2015+A1 EN 60079-31:2014, IEC 60079-31:2013	
EG-Prüfbescheinigung	PTB 14 ATEX 1015 X	
IECEx-Zertifikat	IECEx PTB 14.0027X	

TECHNICAL DATA:


Configuration

Reduction	Polyamide PA6
External thread	metric, as per EN 60423
Internal thread	metric, as per EN 60423

Properties

- reduction of threaded or clearance holes to smaller thread sizes

Group (Zone)	II 2 G (1,2)	II 2 D (21,22)
Marking	Ex e IIC Gb	Ex tb IIIC Db
Temperature range	-55 °C / +70 °C	
Protection grade	IP66, dependent on the combination with other components	
Test standard	EN IEC 60079-0:2018, IEC 60079-0:2017 EN IEC 60079-7:2015+A1, IEC 60079-7:2015+A1 EN 60079-31:2014, IEC 60079-31:2013	
EC-Type certificate	PTB 14 ATEX 1015 X	
IECEx-Certificate	IECEx PTB 14.0027X	



Merkmale

Characteristics

A	B mm	L mm	SW1 mm	H mm		RAL 9005 tiefschwarz jet black Art.-Nr. / Part No.
M16x1,5	M12x1,5	8	24	12	20	GHG9601946R0070
M20x1,5	M12x1,5	8	24	12	20	GHG9601946R0051
M20x1,5	M16x1,5	8	24	12	20	GHG9601946R0071
M25x1,5	M12x1,5	8	29	14	20	GHG9601946R0052
M25x1,5	M16x1,5	8	29	14	20	GHG9601946R0053
M25x1,5	M20x1,5	8	29	14	20	GHG9601946R0072
M32x1,5	M12x1,5	10	36	16	20	GHG9601946R0054
M32x1,5	M16x1,5	10	36	16	20	GHG9601946R0055
M32x1,5	M20x1,5	10	36	16	20	GHG9601946R0056
M32x1,5	M25x1,5	10	36	16	20	GHG9601946R0074
M40x1,5	M16x1,5	10	46	16	10	GHG9601946R0057
M40x1,5	M20x1,5	10	46	16	10	GHG9601946R0058
M40x1,5	M25x1,5	10	46	16	10	GHG9601946R0059
M40x1,5	M32x1,5	10	46	16	10	GHG9601946R0077
M50x1,5	M20x1,5	12	55	18	10	GHG9601946R0060
M50x1,5	M25x1,5	12	55	18	10	GHG9601946R0061
M50x1,5	M32x1,5	12	55	18	10	GHG9601946R0062
M50x1,5	M40x1,5	12	55	18	10	GHG9601946R0080
M63x1,5	M25x1,5	12	68	18	5	GHG9601946R0063
M63x1,5	M32x1,5	12	68	18	5	GHG9601946R0064
M63x1,5	M40x1,5	12	68	18	5	GHG9601946R0065
M63x1,5	M50x1,5	12	68	18	5	GHG9601946R0083