

WAZU-M/EX

Material: Messing vernickelt
 Klemmeinsatz: PA
 Dichtung: NBR
 O-Ring: NBR
 Einsatztemperatur: -20 °C bis 95 °C
 Schutzart: IP 68/IP 69K im angegebenen Klemmbereich

Material: brass, nickel-plated
 Clamping insert: PA (nylon)
 Sealing insert: NBR
 O-ring: NBR
 Temperature range: -20 °C to 95 °C
 Protection type: IP 68/IP 69K within the specified clamping range

154.10

154.30

Zertifikate: DMT 03 ATEX E 051 X
 IECEx BVS 07.0019 X

Certificates: DMT 03 ATEX E 051 X
 IECEx BVS 07.0019 X

Weitere internationale Zulassungen vorhanden

Further international approvals available

Gewinde Entry Thread AG	mm	mm	H mm	GL mm	HSK-M-Ex	HUGRO No.
kurzes Anschlussgewinde / short entry thread						
M 12 x 1,5	2 - 5	14	19	6,5	1.610.1200.51	154.1505.10
M 12 x 1,5	3 - 6,5	14	19	6,5	1.610.1200.50	154.1507.10
M 16 x 1,5	2 - 6	19/17	21	6	1.610.1600.51	154.1706.10
M 16 x 1,5	4 - 8	19/17	21	6	1.610.1600.50	154.1708.10
M 16 x 1,5	6 - 10	20	22	6	1.610.1611.50	154.1710.10
M 20 x 1,5	5 - 9	22	23	6	1.610.2000.51	154.2009.10
M 20 x 1,5	6 - 12	22	23	6	1.610.2000.50	154.2012.10
M 20 x 1,5	10 - 14	24	24	6	1.610.2016.50	154.2014.10
M 25 x 1,5	10 - 16	30	25	7	1.610.2500.51	154.2516.10
M 25 x 1,5	14 - 18	30	25	7	1.610.2500.50	154.2518.10
M 32 x 1,5	13 - 20	40	31	8	1.610.3200.51	154.3220.10
M 32 x 1,5	20 - 25	40	31	8	1.610.3200.50	154.3225.10
M 40 x 1,5	20 - 26	50	37	8	1.610.4000.51	154.4026.10
M 40 x 1,5	22 - 32	50	37	8	1.610.4000.50	154.4032.10
M 50 x 1,5	25 - 31	57	37	9	1.610.5000.51	154.5031.10
M 50 x 1,5	32 - 38	57	37	9	1.610.5000.50	154.5038.10
M 63 x 1,5	29 - 35	68/64	38	10	1.610.6300.51	154.6335.10
M 63 x 1,5	37 - 44	68/64	38	10	1.610.6300.50	154.6344.10

langes Anschlussgewinde / long entry thread						
M 12 x 1,5	2 - 5	14	19	10	1.610.1200.31	154.1505.30
M 12 x 1,5	3 - 6,5	14	19	10	1.610.1200.30	154.1507.30
M 16 x 1,5	2 - 6	19/17	21	10	1.610.1600.31	154.1706.30
M 16 x 1,5	4 - 8	19/17	21	10	1.610.1600.30	154.1708.30
M 16 x 1,5	6 - 10	20	22	10	1.610.1611.30	154.1710.30
M 20 x 1,5	5 - 9	22	23	10	1.610.2000.31	154.2009.30
M 20 x 1,5	6 - 12	22	23	10	1.610.2000.30	154.2012.30
M 20 x 1,5	10 - 14	24	24	10	1.610.2016.30	154.2014.30
M 25 x 1,5	10 - 16	30	25	12	1.610.2500.31	154.2516.30
M 25 x 1,5	14 - 18	30	25	12	1.610.2500.30	154.2518.30
M 32 x 1,5	13 - 20	40	31	12	1.610.3200.31	154.3220.30
M 32 x 1,5	20 - 25	40	31	12	1.610.3200.30	154.3225.30
M 40 x 1,5	20 - 26	50	37	15	1.610.4000.31	154.4026.30
M 40 x 1,5	22 - 32	50	37	15	1.610.4000.30	154.4032.30
M 50 x 1,5	25 - 31	57	37	15	1.610.5000.31	154.5031.30
M 50 x 1,5	32 - 38	57	37	15	1.610.5000.30	154.5038.30
M 63 x 1,5	29 - 35	68/64	38	15	1.610.6300.31	154.6335.30
M 63 x 1,5	37 - 44	68/64	38	15	1.610.6300.30	154.6344.30

Auf Anfrage:
 für Temperaturbereiche
 -60° C bis 95° C
 -20° C bis 130° C

On request:
 for temperature ranges
 -60° C to 95° C
 -20° C to 130° C

