

Progress-M (Pg)

Material: Messing vernickelt
 Dichteinsatz: TPE
 O-Ring: NBR
 Einsatztemperatur: -40 °C bis 100 °C
 Schutzart: IP 68 / IP 69 K

Material: brass, nickel-plated
 Sealing insert: TPE
 O-ring: NBR
 Temperature range: -40 °C to 100 °C
 Protection type: IP 68 / IP 69 K

101.01

101.21

Weitere internationale Zulassungen vorhanden

Further international approvals available



Gewinde Entry Thread AG	 mm	 mm	H mm	Gew. kurz / Thread short GL mm	HUGRO No.	Gew. lang / Thread long GL mm	HUGRO No.
langer, einteiliger Dichteinsatz / long, one-piece sealing insert							
Pg 7	3,5 - 5	15	17	6	101.0705.01		
Pg 7	5 - 6,5	15	17	6	101.0706.01	10	101.0706.21
Pg 7	6,5 - 7,5	15	17	6	101.0708.01	10	101.0708.21
Pg 9	4,5 - 6	18	20	6	101.0906.01		
Pg 9	6 - 8	18	20	6	101.0908.01		
Pg 9	8 - 10,5	18	22	6	101.0910.01	10	101.0910.21
Pg 11	4 - 5,5	21	21	6	101.1105.01		
Pg 11	5,5 - 8,5	21	21	6	101.1108.01		
Pg 11	8,5 - 12	21	21	6	101.1112.01	10	101.1112.21
Pg 13,5	6 - 8	24	21	6	101.1308.01		
Pg 13,5	8 - 11	24	21	6	101.1311.01		
Pg 13,5	11 - 14,5	24	23	6	101.1315.01	10	101.1315.21
Pg 16	6 - 8	24	23	6	101.1608.01		
Pg 16	8 - 11	24	23	6	101.1611.01		
Pg 16	11 - 14,5	24	23	6	101.1615.01	10	101.1615.21
Pg 21	9,5 - 12,5	30	28	7,5	101.2112.01		
Pg 21	12,5 - 16	30	28	7,5	101.2116.01		
Pg 21	16 - 19	30	28	7,5	101.2119.01	12	101.2119.21
Pg 29	19 - 23	38	28	8	101.2923.01		
Pg 29	23 - 27,5	38	28	8	101.2927.01	12	101.2927.21
Pg 36	26 - 30,5	50	32	8	101.3630.01		
Pg 36	30,5 - 35	50	32	8	101.3635.01	15	101.3635.21
Pg 42	33 - 37	55	34	10	101.4237.01		
Pg 42	37 - 42	55	34	10	101.4242.01	15	101.4242.21
Pg 48	37 - 43	65	37	11	101.4843.01		
Pg 48	43 - 49	65	37	11	101.4849.01	15	101.4849.21
langer, zweiteiliger Dichteinsatz / long, two-piece sealing insert							
Pg 9	6 - 10,5	18	22	6	101.0902.01	10	101.0902.21
Pg 11	5,5 - 12	21	21	6	101.1102.01	10	101.1102.21
Pg 13,5	8 - 14,5	24	23	6	101.1302.01	10	101.1302.21
Pg 16	8 - 14,5	24	23	6	101.1602.01	10	101.1602.21
Pg 21	12,5 - 19	30	28	7,5	101.2102.01	12	101.2102.21
Pg 29	19 - 27,5	38	28	8	101.2902.01	12	101.2902.21
Pg 36	26 - 35	50	32	8	101.3602.01	15	101.3602.21
Pg 42	33 - 42	55	34	10	101.4202.01	15	101.4202.21
Pg 48	37 - 49	65	37	11	101.4802.01	15	101.4802.21

Auf Anfrage:

- erhältlich mit Dichteinsatz gemäß EN 45545

On request:

- available with sealing inserts according to EN 45545

