


Material:	Messing vernickelt	Material:	brass, nickel-plated
O-Ring:	NBR	O-ring:	NBR
Einsatztemperatur:	-20 °C bis 120 °C	Temperature range:	-20 °C to 120 °C
Schutzart:	IP 65 - 68	Protection type:	IP 65 - 68
	schuttschlauchabhängig		depending on the conduit type

218.00

Gewinde Entry thread AG	 mm	Ø I mm	d1 mm	H mm	GL mm	HUGRO No.
Pg 7	15	8	9,5	20	6	218.0709
Pg 9	17	7	9	23	6	218.0909
Pg 9	19	10	12	20,5	6	218.0912
Pg 11	22	7	9	20,5	6	218.1109
Pg 11	20	10	12	23	6	218.1112
Pg 11	22	13	15	20,5	6	218.1114
Pg 13,5	24	10	12	20,5	6,5	218.1312
Pg 13,5	22	12	14	22,5	6,5	218.1314
Pg 13,5	22	13	16	22,5	6,5	218.1316
Pg 16	24	12	14	20,5	6,5	218.1614
Pg 16	24	14	16	22,5	6,5	218.1616
Pg 16	24	16	18	22,5	6,5	218.1618
Pg 21	30	19	21	22,5	6,5	218.2121
Pg 21	32	21	24	21	8	218.2124
Pg 29	40	27	29	31,5	7,5	218.2929
Pg 29	40	33	35	31	8	218.2935
Pg 36	50	34	36	32	9	218.3637
Pg 42	60	39	42	50	10	218.4242
Pg 48	64	46	48	27	10	218.4848
Pg 48	64	46	50	32	12	218.4850



Passende Schlauchschellen aus rost-freiem Stahl (1.4016), Schraube aus Stahl verzinkt

Suitable Conduit Clamps made of stain-less steel (1.4016), screw made of galvanized steel

601.00

Spannbereich Chucking capacity	Bandbreite Width	HUGRO No.
10 - 16	7,5	601.1016
12 - 22	9	601.1220
16 - 27	9	601.1625
20 - 32	9	601.2032
25 - 40	9	601.2540
32 - 50	9	601.3250
40 - 60	12	601.4060



Speziell für Kunststoff-Schutzschläuche	Especially for synthetic protective conduits