

Material: Messing vernickelt
Dichtring einfach: Weichgummi
Einsatztemperatur: -20 °C bis 60 °C
Schutzart: IP 54

Material: brass, nickel-plated
Sealing ring simple: soft rubber
Temperature range: -20 °C to 60 °C
Protection type: IP 54

140.00
140.06
140.20
140.26

Gewinde Entry Thread AG			H mm	Gew. kurz / Thread short GL mm	HUGRO No.	Gew. lang / Thread long GL mm	HUGRO No.
einfacher Dichtring / simple sealing ring							
M 12 x 1,5	6 - 8	14 / 16	22	5	140.1507	10	140.1507.20
M 16 x 1,5	8 - 10	18 / 19	25	5	140.1709	10	140.1709.20
M 20 x 1,5	10 - 12	22 / 22	26	6	140.2011	10	140.2011.20
M 20 x 1,5	12 - 13,5	22 / 24	26,5	6	140.2013	10	140.2013.20
M 20 x 1,5	13 - 14,5	24 / 26	28	6	140.2016	10	140.2016.20
M 25 x 1,5	17 - 19	30 / 33	32	7	140.2521	11	140.2521.20
M 32 x 1,5	24 - 26	40 / 42	35	8	140.3229	13	140.3229.20
M 40 x 1,5	33 - 35	50 / 52	41	8	140.4036	13	140.4036.20
M 50 x 1,5	39 - 41	57 / 59	44	9	140.5042	14	140.5042.20
M 63 x 1,5	43 - 45	66 / 64	45	10	140.6348	14	140.6348.20
Pg 7	6 - 8	14 / 16	22	5	140.07	15	140.07.20
Pg 9	8 - 10	17 / 19	25	6	140.09	15	140.09.20
Pg 11	10 - 12	20 / 22	26	6	140.11	15	140.11.20
Pg 13,5	12 - 14	22 / 24	26,5	6,5	140.13	15	140.13.20
Pg 16	14 - 16	24 / 26	28	6,5	140.16	15	140.16.20
Pg 21	17 - 19	30 / 33	32	7	140.21	15	140.21.20
Pg 29	26 - 28	40 / 42	35	8	140.29	15	140.29.20
Pg 36	33 - 35	50 / 52	41	9	140.36	15	140.36.20
Pg 42	39 - 41	57 / 59	44	10	140.42	15	140.42.20
Pg 48	45 - 47	64 / 64	45	10	140.48	15	140.48.20

Universal-Dichtring aus NBR oder CR,
ausschneidbar
Einsatztemperatur: -20 °C bis 80 °C

Universal sealing ring made of NBR or CR,
punchable
Temperature range: -20 °C to 80 °C

M 16 x 1,5	6,5 - 10	18 / 19	25	5	140.1709.06	10	140.1709.26
M 20 x 1,5	7,5 - 12	22 / 22	26	6	140.2011.06	10	140.2011.26
M 20 x 1,5	8,5 - 13,5	22 / 24	26,5	6	140.2013.06	10	140.2013.26
M 20 x 1,5	9,5 - 14,5	24 / 26	28	6	140.2016.06	10	140.2016.26
M 25 x 1,5	12 - 19,5	30 / 33	32	7	140.2521.06	11	140.2521.26
M 32 x 1,5	19 - 26,5	40 / 42	35	8	140.3229.06	13	140.3229.26
M 40 x 1,5	25 - 33,5	50 / 52	41	8	140.4036.06	13	140.4036.26
M 50 x 1,5	31 - 40	57 / 59	44	9	140.5042.06	14	140.5042.26
M 63 x 1,5	35 - 46	66 / 64	45	10	140.6348.06	14	140.6348.26
Pg 9	6,5 - 10	17 / 19	25	6	140.09.06	15	140.09.26
Pg 11	7,5 - 12	20 / 22	26	6	140.11.06	15	140.11.26
Pg 13,5	8,5 - 13,5	22 / 24	26,5	6,5	140.13.06	15	140.13.26
Pg 16	9,5 - 16	24 / 26	28	6,5	140.16.06	15	140.16.26
Pg 21	12 - 20	30 / 33	32	7	140.21.06	15	140.21.26
Pg 29	19 - 28	40 / 42	35	8	140.29.06	15	140.29.26
Pg 36	25 - 34	50 / 52	41	9	140.36.06	15	140.36.26
Pg 42	31 - 40	57 / 59	44	10	140.42.06	15	140.42.26
Pg 48	35 - 46	64 / 64	45	10	140.48.06	15	140.48.26

