




Material: Messing vernickelt  
Dichtring einfach: Weichgummi  
Einsatztemperatur: -20 °C bis 60 °C  
Schutzart: IP 54

Material: brass, nickel-plated  
Sealing ring simple: soft rubber  
Temperature range: -20 °C to 60 °C  
Protection type: IP 54

**121.00**  
**121.06**  
**121.20**  
**121.26**

Gewinde Entry Thread AG			H mm	Gew. kurz / Thread short		Gew. lang / Thread long	
				GL mm	HUGRO No.	GL mm	HUGRO No.
<b>einfacher Dichtring / simple sealing ring</b>							
M 12 x 1,5	4 - 6	14 / 12	16	5	121.15	10	121.15.20
Pg 7	6 - 8	14 / 13	16	5	121.07	15	121.07.20
Pg 9	8 - 10	17 / 15	17	6	121.09	15	121.09.20
Pg 11	10 - 12	20 / 18	18	6	121.11	15	121.11.20
Pg 13,5	12 - 14	22 / 20	19	6,5	121.13	15	121.13.20
Pg 16	14 - 16	24 / 22	20,5	6,5	121.16	15	121.16.20
Pg 21	17 - 19	30 / 28	22,5	7	121.21	15	121.21.20
Pg 29	26 - 28	40 / 37	25	8	121.29	15	121.29.20
Pg 36	33 - 35	50 / 47	30	9	121.36	15	121.36.20
Pg 42	39 - 41	57 / 54	34	10	121.42	15	121.42.20
Pg 48	45 - 47	64 / 60	35	10	121.48	15	121.48.20



Universal-Dichtring aus NBR oder CR,  
ausschneidbar  
Einsatztemperatur: -20 °C bis 80 °C

Universal sealing ring made of NBR or CR,  
punchable  
Temperature range: -20 °C to 80 °C

M 16 x 1,5	2 - 10	18 / 16	16,5	5	121.17.06	10	121.17.26
M 20 x 1,5	3 - 14	22 / 20	19	6	121.20.06	10	121.20.26
M 25 x 1,5	7,5 - 18	27 / 25	22	7	121.25.06	11	121.25.26
M 32 x 1,5	15 - 25	34 / 32	24,5	8	121.32.06	13	121.32.26
M 40 x 1,5	22 - 33	42 / 40	26	8	121.40.06	13	121.40.26
M 50 x 1,5	31 - 42	52 / 50	30	9	121.50.06	14	121.50.26
M 63 x 1,5	40 - 51	66 / 64	35	10	121.63.06	14	121.63.26
<b>Universal-Dichtring aus NBR oder CR, ausschneidbar</b>							
Pg 9	4 - 10	17 / 15	17	6	121.09.06	15	121.09.26
Pg 11	6,5 - 12	20 / 18	18	6	121.11.06	15	121.11.26
Pg 13,5	6,5 - 13,5	22 / 20	19	6,5	121.13.06	15	121.13.26
Pg 16	6,5 - 16	24 / 22	20,5	6,5	121.16.06	15	121.16.26
Pg 21	9 - 20	30 / 28	22,5	7	121.21.06	15	121.21.26
Pg 29	17 - 28	40 / 37	25	8	121.29.06	15	121.29.26
Pg 36	23 - 34	50 / 47	30	9	121.36.06	15	121.36.26
Pg 42	29 - 40	57 / 54	34	10	121.42.06	15	121.42.26
Pg 48	35 - 46	64 / 60	35	10	121.48.06	15	121.48.26

