

Progress-M (Pg)

Material: Messing vernickelt
 Dichteinsatz: TPE
 O-Ring: NBR
 Einsatztemperatur: -40 °C bis 100 °C
 Schutzart: IP 68/IP 69K

Material: brass, nickel-plated
 Sealing insert: TPE
 O-ring: NBR
 Temperature range: -40 °C to 100 °C
 Protection type: IP 68/IP 69K

101.00
101.20

Weitere internationale Zulassungen vorhanden

Further international approvals available



Gewinde Entry Thread AG			H mm	Gew. kurz / Thread short		Gew. lang / Thread long	
				GL mm	HUGRO No.	GL mm	HUGRO No.

kurzer, einteiliger Dichteinsatz / short, one-piece sealing insert							
Pg 7	3,5 - 5	15	17	6	101.0705.00	10	101.0705.20
Pg 7	5 - 6,5	15	17	6	101.0706.00	10	101.0706.20
Pg 7	6,5 - 8	15	17	6	101.0708.00	10	101.0708.20
Pg 9	3,5 - 4,5	18	20	6	101.0904.00	10	101.0904.20
Pg 9	4,5 - 6	18	20	6	101.0906.00	10	101.0906.20
Pg 9	6 - 8	18	20	6	101.0908.00	10	101.0908.20
Pg 9	8 - 10,5	18	22	6	101.0910.00	10	101.0910.20
Pg 11	4 - 5,5	21	21	6	101.1105.00	10	101.1105.20
Pg 11	5,5 - 8,5	21	21	6	101.1108.00	10	101.1108.20
Pg 11	8,5 - 12	21	21	6	101.1112.00	10	101.1112.20
Pg 13,5	6 - 8	24	21	6	101.1308.00	10	101.1308.20
Pg 13,5	8 - 11	24	21	6	101.1311.00	10	101.1311.20
Pg 13,5	11 - 15	24	23	6	101.1315.00	10	101.1315.20
Pg 16	6 - 8	24	23	6	101.1608.00	10	101.1608.20
Pg 16	8 - 11	24	23	6	101.1611.00	10	101.1611.20
Pg 16	11 - 15	24	23	6	101.1615.00	10	101.1615.20
Pg 21	9,5 - 12,5	30	28	7,5	101.2112.00	12	101.2112.20
Pg 21	12,5 - 16	30	28	7,5	101.2116.00	12	101.2116.20
Pg 21	16 - 20,5	30	28	7,5	101.2120.00	12	101.2120.20
Pg 29	16 - 19	38	28	8	101.2919.00	12	101.2919.20
Pg 29	19 - 23	38	28	8	101.2923.00	12	101.2923.20
Pg 29	23 - 27,5	38	28	8	101.2927.00	12	101.2927.20
Pg 36	21,5 - 26	50	32	8	101.3626.00	15	101.3626.20
Pg 36	26 - 30,5	50	32	8	101.3630.00	15	101.3630.20
Pg 36	30,5 - 35	50	32	8	101.3635.00	15	101.3635.20
Pg 42	29 - 33	55	34	10	101.4233.00	15	101.4233.20
Pg 42	33 - 37	55	34	10	101.4237.00	15	101.4237.20
Pg 42	37 - 42	55	34	10	101.4242.00	15	101.4242.20
Pg 48	32 - 37	65	37	11	101.4837.00	15	101.4837.20
Pg 48	37 - 43	65	37	11	101.4843.00	15	101.4843.20
Pg 48	43 - 49	65	37	11	101.4849.00	15	101.4849.20

kurzer, zweiteiliger Dichteinsatz / short, two-piece sealing insert							
Pg 9	6 - 10,5	18	22	6	101.0902.00	10	101.0902.20
Pg 11	5,5 - 12	21	21	6	101.1102.00	10	101.1102.20
Pg 13,5	8 - 15	24	23	6	101.1302.00	10	101.1302.20
Pg 16	8 - 15	24	23	6	101.1602.00	10	101.1602.20
Pg 21	12,5 - 20,5	30	28	7,5	101.2102.00	12	101.2102.20
Pg 29	19 - 27,5	38	28	8	101.2902.00	12	101.2902.20
Pg 36	26 - 35	50	32	8	101.3602.00	15	101.3602.20
Pg 42	33 - 42	55	34	10	101.4202.00	15	101.4202.20
Pg 48	37 - 49	65	37	11	101.4802.00	15	101.4802.20

Auf Anfrage:

- erhältlich mit Dichteinsatz gemäß EN 45545

On request:

- available with sealing inserts according to EN 45545

