

DATENBLATT

N 411

Einbauleuchte für Sternenhimmel




Merkmale:

- Filigraner Lichtpunkt zur Gestaltung eines Sternenhimmels und zur individuellen Effektbeleuchtung
- Aufgrund der geringen Bauhöhe auch für Hohlräume mit geringer Einbautiefe geeignet
- Die Leuchte N 411 kann auch mit einem LED Stiftsockellampe ausgerüstet werden



Technische Daten		Einbauleuchte			
Bezeichnung	N 411				
Artikel Nr.	1855200100	1855200200	1855201000	1855207900	
Farbe	chrom-matt	chrom	weiß	gold	
Oberfläche	galvanisiert	galvanisiert	lackiert	galvanisiert	
Für Leuchtmittel	QT9 Stiftsockellampe/LED Stiftsockellampe				
Fassung	G4				
Nennspannung	12V AC/DC				
Nennleistung	max. 10W				
Material	Zinkdruckguss (Zamak®)				
Schutzklasse	III				
Schutzart	IP20				
Abmessung (Ø)	30 mm				
Deckenausschnitt (Ø)	25 mm				
Einbautiefe	28 mm				
Gewicht	50 g				
Abstand zur beleuchteten Fläche	mind. 0,3 m				
Prüfzeichen	 Einbauleuchte nicht geeignet zur direkten Montage an normal entflammaren Materialien				
	 Einbau an normal entflammaren Materialien nur in Verbindung mit einem LED Leuchtmittel				
CE-Konformität	ja				
Hinweis	beim Einbau auf ein Minimum an Konvektion achten und nicht mit Isoliermaterial abdecken				
Im Lieferumfang enthalten	Lampenfassung und Kabel (30 cm)				



Technische Änderungen vorbehalten.

DATA SHEET

N 411

Recessed downlight for starry sky




Features:

- Filigrane light-point to create a starry night effect or an individual effect lighting
- The low construction allows an installation in minimal mounting depth
- The downlight N 411 can easily be fitted with an LED pin-base lamp



Specifications	Recessed downlight			
Type	N 411			
Part no.	1855200100	1855200200	1855201000	1855207900
Colour	matt chrome	chrome	white	gold
Surface	galvanized	galvanized	painted	galvanized
For light source	QT9 pin-base lamp/LED pin-base lamp			
Lamp holder	G4			
Rated voltage	12V AC/DC			
Rated power	max. 10W			
Material	die-cast zinc(Zamak®)			
Safety class	III			
Protection class	IP20			
Dimension (Ø)	30 mm			
Ceiling cut-out (Ø)	25 mm			
Installation depth	28 mm			
Weight	50 g			
Distance to the lighted objects	min. 0.3 m			
Test marks	 recessed luminaire not suitable for direct mounting on normal flammable surfaces  installation on normal flammable material only in conjunction with an LED lamp			
CE-Conformity	yes			
Note	ensure constant convection and do not cover by insulation material			
Included in delivery	lamp holder and cable (30 cm) approved by VDE, 250°C			



Specifications are subject to change without prior notice.