



FIELDLED II Aufbau, 560 mm, 120°, 24V DC

Artikel-Nr.:	113110-01
EAN:	426055662108

Bestell-Nr.:	113110-01
Modell:	FIELDLED II
Bauform:	LED Aufbauleuchte für Maschinen
Leuchtmittel:	SMD LED
Lampenleistung:	~ 36 W
Lampenlichtstrom:	4752 lm
Lampenlichtausbeute:	132 lm/W
Lichtverteilung:	direkt
Lichtfarbe:	Tageslichtweiß (5200 - 5700K)
Anschlusswert Leuchte:	24V DC $\pm$ 10%
Anschluss Leuchte:	M12 Sensorstecker A-kodiert
Schutzart:	IP69K
Schutzklasse:	III
Entblendung:	opalweiß
Abstrahlwinkel:	120°
Betriebstemperatur:	-30... +55 °C
Farbwiedergabe (Ra):	> 85
Lampenlebensdauer:	> 60.000 h
Material Gehäuse:	Aluminium
Material Abdeckung:	Sicherheitsglas gefrostet, sprungsicher
Höhe [B] x Breite [C]:	30 mm x 96 mm
Länge [A]:	560 mm / 610 mm
Gewicht:	1900 g
Bruttogewicht:	2350 g
Risikogruppe:	freie Gruppe
Kennzeichnung:	CE, ETL Listed
Befestigungszubehör:	Montagewinkel im Lieferumfang
Dimmbar:	optional über Zubehör
Gefertigt in:	Deutschland
Besonderheit:	sehr lichtstark

Lampenlebensdauer in Betriebstunden (L80/B10)



FIELDLED II Aufbau, 560 mm, 120°, 24V DC

Surface-mounted luminaire

Item number:	113110-01
EAN:	426055662108

Order number:	113110-01
Model:	FIELDLED II
Type:	LED surface-mounted luminaire for machines
Illuminant:	SMD LED
Power consumption:	~ 36 W
Lamp luminous flux:	4752 lm
Lamp luminous efficiency:	132 lm/W
Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)
Connected load:	24V DC $\pm$ 10%
Connection (connector):	M12 Sensor connector A-type encoded
Degree of protection:	IP69K
Class of protection:	III
Glare-free	opal white
Beam angle (optics):	120°
Operating temperature:	-30... +55 °C
Colour rendering (Ra):	> 85
Lamps lifetime:	> 60,000 h
Housing material:	aluminium
Cover material:	Safety glass, frosted, shatterproof
Height [B] x Width [C]:	30 mm x 96 mm
Length [A]:	560 mm / 610 mm
Weight (net):	1900 g
Gross weight:	2350 g
Risk group (DIN EN 62471):	free group
Marking:	CE, ETL Listed
Mounting accessories:	Montagewinkel im Lieferumfang
Dimmable:	via optional accessory
Made in:	Germany
Feature:	very bright

Lamps lifetime in operation hours (L80/B10)