



LED Arbeitsplatzleuchte
LED workplace luminaire



**SYSTEMLED Power, 898 mm, 4000-4500K,
matte cover**

Item number: 141024-01
EAN: 4260556620466

Order number: 141024-01
Model: SYSTEMLED
Type: LED system luminaire
Illuminant: SMD LED
Power consumption: ~52 W
Lamp luminous flux: 5356 lm
Lamp luminous efficiency: 131 lm/W
Light distribution: direct
Light colour: neutral white (4000 - 4500K)
Connected load: 220-240V AC ± 10%, 50-60 Hz
Power supply: inbuilt
Connection (connector): Wieland GST18
Degree of protection: IP40
Class of protection: I
Glare-free: opal white
Beam angle (optics): 100°
Operating temperature: -10... +50 °C
Colour rendering (Ra): > 90
Lamps lifetime: > 60,000 h
Housing material: aluminium
Height [B] x Width [C]: 40 mm x 138 mm
Length [A]: 898 mm
Weight (net): 2550 g
Gross weight: 3500 g
Risk group (DIN EN 62471): free group
Mounting accessories: optional
Dimmable: via optional accessory
Marking: CE
Made in: Germany
Feature: cascadable



You can interlink several luminaires electrically (cascadable). 230V mains voltage is applied to the first luminaire and additionally Wieland extension cables are used to connect further luminaires to each other via the inputs and outputs in the luminaire housing. The total current of the interlinked luminaires must not exceed the fuse rating of the 230V connection on the operating side.

Lamps lifetime in operation hours (L80/B10)