



LED Industrieleuchte

LED industrial luminaire



INROLED_25, 552 mm, 100°, 24V DC

Artikel-Nr.: 117110-01
EAN: 4260556621562

Bestell-Nr.:	117110-01
Modell:	INROLED_25
Bauform:	LED Rohrleuchte
Leuchtmittel:	SMD LED
Lampenleistung:	~7,5 W
Lampenlichtstrom:	972 lm
Lampenlichtausbeute:	129 lm/W
Lichtverteilung:	direkt
Lichtfarbe:	Tageslichtweiß (5200 - 5700K)
Anschlusswert Leuchte:	24V DC \pm 10%
Anschluss Leuchte:	M12 Steckverbinder A-kodiert
Schutzart:	IP69K
Schutzklasse:	III
Entblendung:	opalweiß
Abstrahlwinkel:	100°
Betriebstemperatur:	-10... +35 °C
Farbwiedergabe (Ra):	> 80
Lampenlebensdauer:	> 60.000 h
Material Abdeckung:	Polycarbonat, splitterfrei
Höhe [B] x Breite [C]:	\varnothing 25 mm
Länge [A]:	552 mm
Gewicht:	250 g
Bruttogewicht:	400 g
Risikogruppe:	freie Gruppe
Befestigungszubehör:	Halterung inkl.
Dimmbar:	optional über Zubehör
Kennzeichnung:	CE, ETL Listed
Gefertigt in:	Deutschland
Besonderheit:	Lebensmittelrecht, beständig gegen Säure und Laugen (vorab Einzelfallprüfung)


Lampenlebensdauer in Betriebsstunden (L80/B10)



INROLED_25, 552 mm, 100°, 24V DC

Item number: 117110-01
EAN: 4260556621562

Order number:	117110-01
Model:	INROLED_25
Type:	LED tube luminaire
Illuminant:	SMD LED
Power consumption:	~7,5 W
Lamp luminous flux:	972 lm
Lamp luminous efficiency:	129 lm/W
Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)
Connected load:	24V DC \pm 10%
Connection (connector):	M12 connector A-type encoded
Degree of protection:	IP69K
Class of protection:	III
Glare-free	opal white
Beam angle (optics):	100°
Operating temperature:	-10... +35 °C
Colour rendering (Ra):	> 80
Lamps lifetime:	> 60,000 h
Cover material:	polycarbonate, shatterproof
Height [B] x Width [C]:	\varnothing 25 mm
Length [A]:	552 mm
Weight (net):	250 g
Gross weight:	400 g
Risk group (DIN EN 62471):	free group
Mounting accessories:	incl. luminaire holders
Dimmable:	via optional accessory
Marking:	CE, ETL Listed
Made in:	Germany
Feature:	food-safe, resistant to acids and alkalis (case-by-case testing before)



Lamps lifetime in operation hours (L80/B10)