

**Special features**

- Robust housing
- Flicker-free
- Secured against short circuits and overloads
- Overheating protection

<b>Housing Material</b>	Aluminium
<b>Housing Color</b>	Grey
<b>Operating Mode</b>	Constant voltage
<b>Protection Class</b>	Protection class I/protective grounding
<b>Power</b>	320 W
<b>Output Voltage</b>	24 V/DC
<b>Output Current</b>	0-13340 mA
<b>Power Factor</b>	0.95
<b>Primary Connection</b>	With free strand / conductor ends
<b>Secondary Connection</b>	Open cables
<b>Max. units per MCB B10</b>	1
<b>Max. units per MCB B16</b>	2
<b>Max. units per MCB C10</b>	2
<b>Max. units per MCB C16</b>	4
<b>Inrush Current max.</b>	70 A / 500 $\mu$ s
<b>Capacitive Load</b>	626.3 nF
<b>Reference Point Tc</b>	90 °C
<b>Working Temperature</b>	-40 to 50 °C
<b>Storage Temperature</b>	-20 to 70 °C
<b>IP Protection Class</b>	IP 67
<b>Life Time</b>	50000 h
<b>Length</b>	252 mm
<b>Width</b>	90 mm
<b>Height</b>	44 mm
<b>Product weight</b>	1748 g

