

LED Arbeitsplatzleuchte


LED workplace luminaire



PROFILED DC, 1200 mm, mit Dimmer, Abdeckung Mikroprismen, 24V DC


Artikel-Nr.: 150814-02
EAN: 4260556623849

| | |
|-------------------------------|--|
| Bestell-Nr.: | 150814-02 |
| Modell: | PROFILED |
| Bauform: | Profilleuchte mit T-Nut rückseitig |
| Leuchtmittel: | SMD LED |
| Lampenleistung: | ~32 W |
| Lampenlichtstrom: | 4410 lm |
| Lampenlichtausbeute: | 145 lm/W |
| Lichtverteilung: | direkt |
| Lichtfarbe: | Tageslichtweiß (5200 - 5700K) |
| Anschlusswert Leuchte: | 24V DC ± 10% |
| Anschluss Leuchte: | M12 Steckverbinder A-kodiert |
| Schutzart: | IP40 |
| Schutzklasse: | III |
| Entblendung: | Mikroprismen |
| Abstrahlwinkel: | 100° |
| Betriebstemperatur: | -10... +60 °C |
| Farbwiedergabe (Ra): | > 85 |
| Lampenlebensdauer: | > 60.000 h |
| Material Gehäuse: | Aluminium |
| Material Abdeckung: | Kunststoff |
| Höhe [B] x Breite [C]: | 65 mm x 45 mm |
| Länge [A]: | 1200 mm |
| Gewicht: | 2100 g |
| Bruttogewicht: | 2850 g |
| Risikogruppe: | freie Gruppe |
| Befestigungszubehör: | optional |
| Dimmbar: | Dimmer intern |
| Kennzeichnung: | CE |
| Gefertigt in: | Deutschland |
| Besonderheit: | mit Dimmung, universell als Werkbankleuchte, Systemleuchte oder Industrieleuchte |



Lampenlebensdauer in Betriebsstunden (L80/B10)


LED Arbeitsplatzleuchte
LED workplace luminaire



**PROFILED DC, 1200 mm, with dimmer
micro prisms cover, 24V DC**

Item number: 150814-02
EAN: 4260556623849

| | |
|-----------------------------------|--|
| Order number: | 150814-02 |
| Model: | PROFILED |
| Type: | profiled luminaire with t-slot backsided |
| Illuminant: | SMD LED |
| Power consumption: | ~32 W |
| Lamp luminous flux: | 4410 lm |
| Lamp luminous efficiency: | 145 lm/W |
| Light distribution: | direct |
| Light colour: | daylight white (5200 - 5700K) |
| Connected load: | 24V DC ± 10% |
| Connection (connector): | M12 A-type encoded |
| Degree of protection: | IP40 |
| Class of protection: | III |
| Glare-free | micro prisms |
| Beam angle (optics): | 100° |
| Operating temperature: | -10... +60 °C |
| Colour rendering (Ra): | > 85 |
| Lamps lifetime: | > 60,000 h |
| Housing material: | aluminium |
| Cover material: | plastics |
| Height [B] x Width [C]: | 65 mm x 45 mm |
| Length [A]: | 1200 mm |
| Weight (net): | 2100 g |
| Gross weight: | 2850 g |
| Risk group (DIN EN 62471): | free group |
| Mounting accessories: | optional |
| Dimmable: | internal dimmer control |
| Marking: | CE |
| Made in: | Germany |
| Feature: | with dimming control, universally accepted as workbench lighting, system luminaire or industrial light |



Lamps lifetime in operation hours (L80/B10)