


LED Industrielleuchte  
 LED industrial luminaire


## INROLED\_50 Ecolab, 1065 mm, 230V AC

**Artikel-Nr.:** 110210-03  
**EAN:** 4260556624679

|                               |   |
|-------------------------------|---|
| <b>Bestell-Nr.:</b>           | 110210-03   |
| <b>Modell:</b>                | INROLED_50  |
| <b>Bauform:</b>               | LED Rohrleuchte   |
| <b>Leuchtmittel:</b>          | SMD LED   |
| <b>Lampenleistung:</b>        | ~32 W   |
| <b>Lampenlichtstrom:</b>      | 5120 lm   |
| <b>Lampenlichtausbeute:</b>   | 127 lm/W  |
| <b>Lichtverteilung:</b>       | direkt  |
| <b>Lichtfarbe:</b>            | Tageslichtweiß (5200 - 5700K)                                 |
| <b>Anschlusswert Leuchte:</b> | 220-240V AC ± 10%, 50-60 Hz                                   |
| <b>Betriebsgerät:</b>         | integriert  |
| <b>Anschluss Leuchte:</b>     | M12 S-kodiert   |
| <b>Schutzart:</b>             | IP67/IP69K  |
| <b>Schutzklasse:</b>          | I   |
| <b>Entblendung:</b>           | opalweiß  |
| <b>Abstrahlwinkel:</b>        | 100°  |
| <b>Betriebstemperatur:</b>    | -30... +30 °C   |
| <b>Farbwiedergabe (Ra):</b>   | > 80  |
| <b>Lampenlebensdauer:</b>     | > 50.000 h  |
| <b>Schlagfestigkeit:</b>      | IK09  |
| <b>Material Abdeckung:</b>    | Polycarbonat, matt, splitterfrei mit Ecolab-Beschichtung      |
| <b>Höhe [B] x Breite [C]:</b> | Ø 50 mm   |
| <b>Länge [A]:</b>             | 1065 mm   |
| <b>Gewicht:</b>               | 1650 g  |
| <b>Bruttogewicht:</b>         | 1950 g  |
| <b>Risikogruppe:</b>          | freie Gruppe  |
| <b>Befestigungszubehör:</b>   | Leuchtenhalter aus metalldektierbaren PP inklusive            |
| <b>Kennzeichnung:</b>         | CE  |
| <b>Gefertigt in:</b>          | Deutschland   |
| <b>Besonderheit:</b>          | Food+Beverage geeignet: Ecolab zertifiziert, HACCP-Zertifikat |




Lampenlebensdauer in Betriebsstunden (L80/B10)



## INROLED\_50 Ecolab, 1065 mm, 230V AC

**Item number:** 110210-03  
**EAN:** 4260556624679

|                                   |   |
|-----------------------------------|---|
| <b>Order number:</b>              | 110210-03   |
| <b>Model:</b>                     | INROLED_50  |
| <b>Type:</b>                      | LED tube luminaire  |
| <b>Illuminant:</b>                | SMD LED   |
| <b>Power consumption:</b>         | ~32 W   |
| <b>Lamp luminous flux:</b>        | 5120 lm   |
| <b>Lamp luminous efficiency:</b>  | 127 lm/W  |
| <b>Light distribution:</b>        | direct  |
| <b>Light colour:</b>              | daylight white (5200 - 5700K)                               |
| <b>Connected load:</b>            | 220-240V AC ± 10%, 50-60 Hz                                 |
| <b>Power supply:</b>              | inbuilt   |
| <b>Connection (connector):</b>    | M12 connector S-type encoded                                |
| <b>Degree of protection:</b>      | IP67/IP69K  |
| <b>Class of protection:</b>       | I   |
| <b>Glare-free</b>                 | opal white  |
| <b>Beam angle (optics):</b>       | 100°  |
| <b>Operating temperature:</b>     | -30... +30 °C   |
| <b>Colour rendering (Ra):</b>     | > 80  |
| <b>Lamps lifetime:</b>            | > 50,000 h  |
| <b>Impact-resistant:</b>          | IK09  |
| <b>Cover material:</b>            | polycarbonate, milky, shatterproof with Ecolab coating      |
| <b>Height [B] x Width [C]:</b>    | Ø 50 mm   |
| <b>Length [A]:</b>                | 1065 mm   |
| <b>Weight (net):</b>              | 1650 g  |
| <b>Gross weight:</b>              | 1950 g  |
| <b>Risk group (DIN EN 62471):</b> | free group  |
| <b>Mounting accessories:</b>      | incl. luminaire holder made of metal detectable PP          |
| <b>Marking:</b>                   | CE  |
| <b>Made in:</b>                   | Germany   |
| <b>Feature:</b>                   | Food+Beverage suitable: Ecolab certified, HACCP certificate |



Lamps lifetime in operation hours (L80/B10)