


LED Industrieleuchte
 LED industrial luminaire


INROLED_50 Ecolab Power, 565 mm, 24V DC

Artikel-Nr.: 110110-01
EAN: 4260556624631

| | |
|-------------------------------|---|
| Bestell-Nr.: | 110110-01 |
| Modell: | INROLED_50 |
| Bauform: | LED Rohrleuchte |
| Leuchtmittel: | SMD LED |
| Lampenleistung: | ~24 W |
| Lampenlichtstrom: | 3217 lm |
| Lampenlichtausbeute: | 131 lm/W |
| Lichtverteilung: | direkt |
| Lichtfarbe: | Tageslichtweiß (5200 - 5700K) |
| Anschlusswert Leuchte: | 24V DC \pm 10% |
| Anschluss Leuchte: | M12 A-kodiert |
| Schutzart: | IP67/IP69K |
| Schutzklasse: | III |
| Entblendung: | opalweiß |
| Abstrahlwinkel: | 100° |
| Betriebstemperatur: | -30... +50 °C |
| Farbwiedergabe (Ra): | > 85 |
| Lampenlebensdauer: | > 60.000 h |
| Schlagfestigkeit: | IK09 |
| Material Abdeckung: | Polycarbonat, matt, splitterfrei mit Ecolab-Beschichtung |
| Höhe [B] x Breite [C]: | \varnothing 50 mm |
| Länge [A]: | 565 mm |
| Gewicht: | 950 g |
| Bruttogewicht: | 1150 g |
| Risikogruppe: | freie Gruppe |
| Befestigungszubehör: | Leuchtenhalter aus metalldektierbaren PP inklusive |
| Dimmbar: | optional über Zubehör |
| Kennzeichnung: | CE, ETL Listed |
| Gefertigt in: | Deutschland |
| Besonderheit: | Food+Beverage geeignet: Ecolab zertifiziert, HACCP-Zertifikat |




Lampenlebensdauer in Betriebsstunden (L80/B10)



INROLED_50 Ecolab Power, 565 mm, 24V DC

Item number: 110110-01
EAN: 4260556624631

| | |
|-----------------------------------|---|
| Order number: | 110110-01 |
| Model: | INROLED_50 |
| Type: | LED tube luminaire |
| Illuminant: | SMD LED |
| Power consumption: | ~24 W |
| Lamp luminous flux: | 3217 lm |
| Lamp luminous efficiency: | 131 lm/W |
| Light distribution: | direct |
| Light colour: | daylight white (5200 - 5700K) |
| Connected load: | 24V DC ± 10% |
| Connection (connector): | M12 connector A-type encoded |
| Degree of protection: | IP67/IP69K |
| Class of protection: | III |
| Glare-free | opal white |
| Beam angle (optics): | 100° |
| Operating temperature: | -30... +50 °C |
| Colour rendering (Ra): | > 85 |
| Lamps lifetime: | > 60,000 h |
| Impact-resistant: | IK09 |
| Cover material: | polycarbonate, milky, shatterproof with Ecolab coating |
| Height [B] x Width [C]: | Ø 50 mm |
| Length [A]: | 565 mm |
| Weight (net): | 950 g |
| Gross weight: | 1150 g |
| Risk group (DIN EN 62471): | free group |
| Mounting accessories: | incl. luminaire holder made of metal detectable PP |
| Dimmable: | via optional accessory |
| Marking: | CE, ETL Listed |
| Made in: | Germany |
| Feature: | Food+Beverage suitable: Ecolab certified, HACCP certificate |



Lamps lifetime in operation hours (L80/B10)