
TugraHE 21 PW 64-840 ET 23

TOC: 8002640





Product features and key data

Luminaire type	Multi-variable and modern tube luminaire with 75 mm profile diameter.
Mounting method	Surface-mounting|Suspension
Luminaire optic	Cylindrical profile with photometrically effective prismatic structure as secondary optic.
Connected load	34 W
Power factor	0,95
Colour temperature	4.000 K
Rated luminous flux	6.400 lm
Luminous efficacy	188 lm/W
Interchangeability lightsource	Yes - interchangeable
Service life	L80 (25 °C) = 70.000 h
Colour rendering index	80
Colour tolerance	3 SDCM
Photobiological class	Group 0 - no risk
Luminaire colour	RAL7035 Light grey
Luminaire body	PMMA luminaire profile.
Electrical version	With electronic transformer, switchable.
Connection method	Plug-in terminal
Mains frequency	50/60 Hz
Mains voltage	220 - 240 V
Ingress Protection (IP) rating	IP66
Protection rating on room side	IP66
Protection class	I
Impact resistance (IK)	IK03
Hot wire resistance	650 °C
Ambient temperature	-30 - 35 °C
Max. Luminaires B10	18
Max. Luminaires B16	30
Max. Luminaires C10	31
Max. Luminaires C16	51
Net length	2.130 mm
Net width	75 mm
Net height	75 mm
Outside diameter	75 mm
Weight	4,7 kg

Available accessories

Material	Description
Tugra ZLV/315/21 8117500	Through-wiring, 3-core. For luminaires from seriesTugra 21... .
Tugra ZLV/515/21 8117600	Through-wiring, 5-core. For luminaires from seriesTugra 21... .

All technical data including details of weight and dimensions have been compiled with all due care. Errors excepted. Product illustrations serve as examples and may differ from the original. We reserve the right to make alterations in the interest of improving our products.

Tugra ZLV/715/21 8117700	Through-wiring, 7-core. For luminaires from seriesTugra 21... .
Tugra BLP 1165 PL 8100300	Blank module for continuous line applications. Cover of highly impact-resistant PMMA, opal. Module length 1165 mm.
Tugra ZSDT/2000 8117800	Wire suspension for luminaires of series Tugra. With loop for ceiling suspension. With metal clamp for use of triangle.
Tugra ZSDD/2000 8117900	Wire suspension for luminaires of series Tugra. With decorative ceiling connection. With threaded sleeve for attachment to mounting clip.
Tugra ZSSD/2000 8118000	Wire suspension for luminaires of series Tugra. With loop for ceiling suspension. With threaded sleeve for attachment to mounting clip.
Tugra ZBRS 8118100	Tube clip for wall and ceiling mounting and also suitable for suspended mounting by means of separate accessories. Packaging unit has 1 piece.
Tugra ZBWM 8118200	Pivotable mounting brackets for wall mounting. Packaging unit 2 pieces.
Tugra ZB V2A 8118300	Standard stainless steel mounting clips (2 pieces, V2A) for wall and ceiling fixing with triangle for holding components for suspended mounting.
Tugra ZB V4A 8118400	Stainless steel mounting clips (2 pieces, V4A) for wall and ceiling fixing with triangle for holding components for suspended mounting. Design is particularly suitable for use in environments with chlorine and saline atmospheres.
Tugra ZBATL 8118500	Disassembly protection for horizontal wall mounting. 1 set= 2 pieces.
Tugra ZSST/2000 8118900	Wire suspension for luminaires of series Tugra. With decorative ceiling connection. With metal clamp for use of triangle.

Offer text

Multi-variable and modern tube luminaire with 75 mm profile diameter. Suitable for use in HACCP, IFS version 6 and/or BRC Global Standard Food version 7 certified companies (DIN 10500). Luminaire with limited surface temperature in accordance with DIN EN 60598-2-24, suitable for use in work locations exposed to fire hazards. For wall and ceiling mounting. Standard stainless steel mounting clips (2 pieces, V2A) with triangle included in the scope of supply. Optional accessories enable further mounting concepts. As single luminaire or for continuous line use. The continuous mounting channel of the luminaire body enables very high flexibility in positioning the fixing points. The packaging is made of recyclable cardboard, plastic-free. Multiple packaging with 28 luminaires as well as project packaging with 108 luminaires per packaging unit further reduce the general consumption of resources in the overall process. Cylindrical profile with photometrically effective prismatic structure as secondary optic. With opal profile area above and translucent profile area below the mounting channel. With wide light distribution. With mainly direct light distribution. With slight indirect component for decorative surface illumination. Luminaire luminous flux 6400 lm, connected load 34,00 W, luminous efficiency of luminaire 188 lm/W. Light colour neutral white, correlated colour temperature (CCT) 4000 K, general colour rendering index (CRI) R_a > 80. Colour locus tolerance (initial MacAdam) ≤ 3 SDCM, Mean rated service life L80(t_q 25 °C) = 70,000 h. The light source is replaceable according to the ecodesign requirements (VO (EU) 2019/2020). PMMA luminaire profile. End cap colour light grey, (RAL 7035). End cap made of thermoplastically fused PMMA / TPE with high-quality, matt surface structure and surface finish according to VDI24. The end cap is equipped with 3 self-sealing membranes for cable cross-sections 7 mm - 13 mm as well as 3 pre-stamped feed points for PG cable glands (M20/M25) for protection rating-compliant infeed (IP66). The end cap is connected to the profile cylinder via a bayonet lock. Standard end caps included. Luminaire length 2130 mm, Luminaire height 75 mm, Ø Luminaire body 75 mm. The gear tray is fixed to the luminaire profile with transparent devices to avoid shadowing. Permissible ambient temperature (ta) -30 °C - 35 °C. Safety class (EN 61140): I, protection rating (DIN EN 60529): IP66, impact resistance level in accordance with IEC 62262: IK03, testing temperature of wire glow test in accordance with IEC 60695-2-11: 650 °C. Weight: 4,7 kg. The connection is made by means of a plug-in terminal with mains forwarding equipment. The barrier free cable duct inside the luminaire profile facilitates the insertion of optional through-wiring or alternative uses, e.g. installing network cables. With electronic transformer, switchable. The ENEC certification by an independent testing laboratory is in preparation. The luminaire complies with the fundamental requirements of applicable EU regulations and product safety legislation and bears the CE symbol.

EPREL ID

D: 85400877

D: 85400879

All technical data including details of weight and dimensions have been compiled with all due care. Errors excepted. Product illustrations serve as examples and may differ from the original. We reserve the right to make alterations in the interest of improving our products.