

Sheet 1 of 3

Technical Data


General Data	
Connection	1:1
Colors	white, black, gray, red, yellow, green, blue, turquoise, violet, orange
Identification possibility	Colorclips (Order No.: CPZHS7BOX)
Cable Characteristics	
Cable type	S/FTP
Number twisting elements	4P+1
Twisting elements	Pair
Configuration	LSHF (LSOH) acc. EN50290-2-27
Braid	AWG26/7
Category	Cat. 6 ISO/IEC
Shielding	shielded
Connector Characteristics	
Housing material	Polycarbonate
Pin plating	Au (Gold)
Environmental Conditions	
Temperature range during operation	-25°C to + 60°C
Temperature range during installation	0°C to + 50°C
Approvals	
RoHS	conform
Standards	
General requests	ISO/IEC 11801 Ed.2.2: 2011-06 DIN EN 50173-1: 2011-09 TIA/EIA 568-C.2 IEC 60332-1
Plug	DIN EN 60603-7
Transmission Characteristics	
Category (ISO)	6
Category (TIA)	6
Remote powering	yes
PoE	IEEE 802.3af
PoE +	IEEE 802.3at
PoE ++	IEEE 802.3bt
UPoE	yes
HDBaseT	yes
Bit rate up to 10 GBit	IEEE 802.3an

d c b a	Änderung Änderung Änderung Neuerstellung
--	--

Technical Data


Electrical Characteristics	
Loop resistance	290 Ω/km
Insulation resistance	≥5000 MΩ*km
Characteristic impedance	100 ± 3Ω
Propagation delay	10ns / 100m
Packaging Unit	0,1 m - ≤5,0 m = 5 pcs >5,0 m = 1 pc

Drawing



Color	Order No.
white	CP1KWDWDW0000*
black	CP1KSDSDS0000*
gray	CP1KADADA0000*
red	CP1KRDRDR0000*
yellow	CP1KYDYDY0000*
green	CP1KGDGDG0000*
blue	CP1KBDBDB0000*
turquoise	CP1KTDTDT0000*
violet	CP1KVDVDV0000*
orange	CP1KODODO0000*

*Length in dm
e.g. 0010 = 1 m



dimension RJ45
according to IEC 60603-7

d c b a	Änderung Änderung Änderung Neuerstellung	12.02.2026 15.11.2021 22.08.2019 20.02.2017	MW MW LP LP	drawn	20.02.2017	LP
				appr.	20.02.2017	MJ
				Titel: EasyLan® Patch Cord FlexBoot Cat.6 ISO/IEC		
				Drawing Number: ZN-CU181260		
Index	Revision Code	Date	Name	 EasyLan® ...for a better connectivity		
				Dimensions: mm		
				Original: DIN A4		
				Sheet 3 of 3		

